



## ECH20 10HS LARGE VOLUME SOIL MOISTURE SENSING

### DESCRIPTION

The 10-cm long 10HS has three times the volume of influence compared to smaller sensors, measuring one liter of soil volume. Most soil sensors that measure this much volume are 20 cm or longer, causing installation headaches. The 10HS provides the perfect balance between volume of influence and sensor size, installing easily into the sidewall of a narrow trench.

The 10HS measures volumetric water content by means of capacitance technology. Its high measurement frequency minimizes salinity and textural effects, making this sensor accurate in a large range of mineral soils.



### 10HS

#### FEATURES

- Large volume of influence
- High measurement frequency
- Easy to install
- Plug and play capability with METER loggers
- Simple integration with third-party loggers as a single-ended voltage reading

Soil is highly variable in space. The 10HS soil moisture probe with its larger volume of influence can smooth variability and accurately characterize highly heterogeneous soil water content. It's the perfect balance between volume of influence, accuracy, affordability, and ease of installation.

# 10HS Soil Moisture Sensor

A special coating makes the 10HS soil moisture sensor resistant to salts. Very low power consumption and a high resolution provide increased precision over a longer period of time.

Push the 10HS directly into undisturbed soil, plug it in, and start collecting data. It's that easy with the METER ZL6 data logging system.

## Contact info



### Monitoring MENA

Insight into instrumentations

**(962) 5353-2091**

PO Box 1100 Salt

Post Code 19110 JORDAN

[sales@monitoring-mena.com](mailto:sales@monitoring-mena.com)

[www.monitoring-mena.com](http://www.monitoring-mena.com)

SPECIFICATIONS	
Volumetric water content (VWC)	<p><b>RANGE:</b>                      Mineral soil calibration: 0–0.57 m<sup>3</sup>/m<sup>3</sup> (0%–57% VWC)                      Soilless media calibration: 0–0.69 m<sup>3</sup>/m<sup>3</sup> (0%–69% VWC)                      Apparent dielectric permittivity (<math>\epsilon_a</math>): 1 (air) to 80 (water)  <b>NOTE: The VWC range is dependent on the media the sensor is calibrated to. A custom calibration will accommodate the necessary ranges for most substrates.</b>  <b>RESOLUTION:</b>                      0.0008 m<sup>3</sup>/m<sup>3</sup> (0.08% VWC) in mineral soils from 0–0.50 m<sup>3</sup>/m<sup>3</sup> (0%–50% VWC)  <b>ACCURACY:</b>                      With standard calibration equation, 0.03 m<sup>3</sup>/m<sup>3</sup> (3% VWC) typical in mineral soils that have solution electrical conductivity &lt;10 dS/m  <b>NOTE: With soil-specific calibration, <math>\pm 0.02</math> m<sup>3</sup>/m<sup>3</sup> (<math>\pm 2\%</math> VWC) is typical in any soil.</b></p>
Measurement volume	See <a href="#">comparison article</a>
COMMUNICATION SPECIFICATIONS	
Output	300–1,250 mV, independent of excitation voltage
Data logger compatibility	METER data loggers (ZL6, EM50/60 series, Em5b) or any data acquisition systems capable of switched 3–15 VDC excitation and single-ended voltage measurement at greater than or equal to 12-bit resolution.
PHYSICAL SPECIFICATIONS	
Dimensions	Length: 16.0 cm (6.3 in) Width: 3.3 cm (1.3 in) Height: 0.8 cm (0.3 in)
Prong length	10 cm (3.94 in)
Operating temperature range	Minimum: –40 °C Typical: NA Maximum: 50 °C <b>NOTE: Sensors may be used at higher temperatures under certain conditions; contact Customer Support for assistance.</b>
Cable length	5 m (standard) 40 m (maximum custom cable length) <b>NOTE: Contact Customer Support if a nonstandard cable length is needed.</b>
Connector types	3.5-mm stereo plug connector or stripped and tinned wires
ELECTRICAL AND TIMING CHARACTERISTICS	
Supply voltage (VIN to GND)	Minimum: 3 VDC Typical: NA Maximum: 15 VDC
Measurement duration	Maximum 10 ms
	Manufactured under ISO 9001:2015

This Instrument is manufactured by our principle company

**METER Environment - USA**